



Sakrete® U.S. Cold Patch® is a revolutionary ready-to-use recycled asphalt product for permanently repairing potholes, cracks, and other defects in asphalt and concrete surfaces. Sakrete U.S. Cold Patch is ready to drive on immediately after application. Sakrete U.S. Cold Patch is dry, odorless, and contains none of the hazardous volatiles found in typical cold asphalts. Tests have proven that Sakrete U.S. Cold Patch is stronger, easier to use, and much safer than other comparable products.

FEATURES:

- Once compacted, Sakrete U.S. Cold Patch becomes as hard as hot asphalt
- Can be used in all weather conditions
- Ready to drive on immediately after application

USE FOR:

- Potholes

COVERAGE: U.S. Cold Patch is designed to repair pot holes. For other uses please contact Sakrete (1-866 Sakrete) to discuss the advisability of your particular application.

Depth	2 ft ²	4 ft ²	6 ft ²
2"	1 bag	2 bags	3 bags
3"	2 bags	3 bags	4 bags
4"	2 bags	5 bags	6 bags

PREPARATION:

- Sweep area to be repaired. Be sure to remove all loose material.

NOTE: it is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.

APPLICATION:

1. For repairs over 2" deep, it is very important to apply this material in 1 - 2 lifts (layers).

2. Pour some material into the hole, compact it with a post or tamper and repeat until the area is repaired.
3. Finished patch should be slightly crowned above surrounding surface.
4. Compact with a tamper, a shovel or by driving over the area with the wheels of your car. Return any unused product to bag and store for future use.

SAFETY:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). **KEEP OUT OF REACH OF CHILDREN.**

LIMITED PRODUCT WARRANTY:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

